

缓冲式防回转金属配件吸盘 /NAPWTH · YH

型号

① ② ③ ④
 NAPW T H - 4 × 10-3 - N - T

①真空接口方向

T	纵向接口
Y	横向接口

②吸盘直径 · 行程 (短径 × 长径)mm

4 × 10-3	6 × 10-3
4 × 10-10	6 × 10-10
4 × 10-15	6 × 10-15
4 × 20-3	6 × 20-3
4 × 20-10	6 × 20-10
4 × 20-15	6 × 20-15
4 × 30-3	6 × 30-3
4 × 30-10	6 × 30-10
4 × 30-15	6 × 30-15
5 × 10-3	8 × 20-3
5 × 10-10	8 × 20-10
5 × 10-15	8 × 20-15
5 × 20-3	8 × 30-3
5 × 20-10	8 × 30-10
5 × 20-15	8 × 30-15
5 × 30-3	
5 × 30-10	
5 × 30-15	

③吸盘橡胶材质

N	丁腈橡胶
S	硅橡胶
U	聚氨酯橡胶

注)上面以外的材质也可以制作, 请与本公司协商。

④接头

无记号	无
T	笋形接头
O	快速接头

金属配件规格

吸盘直径		4 × 10 ~ 8 × 30		
真空接口方向		纵	横	
配管接头	无接头	M5	M5	
	笋形接头	φ 4 × 2.5	×	×
		φ 6 × 4	○ (M5)	○ (M5)
	快速接头	φ 4 × 2.5	×	×
		φ 6 × 4	○ (M5)	○ (M5)
金属配件安装方法		公螺纹	公螺纹	

吸盘标准规格

记号	材质	硬度(Hs)	使用温度范围	颜色	体积电阻率
N	丁腈橡胶	A55/S	-26 ~ 120℃	黑色	—
S	硅橡胶	A55/S	-60 ~ 250℃	乳白色	—
U	聚氨酯橡胶	A55/S	-20 ~ 75℃	蓝色	—

金属配件对应一览

	型号	长圆形吸盘											
		4 × 10	4 × 20	4 × 30	5 × 10	5 × 20	5 × 30	6 × 10	6 × 20	6 × 30	8 × 20	8 × 30	
金属配件	纵向接口	NAPWTH-4 × 10-3-K	○			○		○					
		NAPWTH-4 × 10-10-K	○			○		○					
		NAPWTH-4 × 10-15-K	○			○		○					
		NAPWTH-4 × 20-3-K		○			○			○		○	
		NAPWTH-4 × 20-10-K		○			○			○		○	
		NAPWTH-4 × 20-15-K		○			○			○		○	
		NAPWTH-4 × 30-3-K			○			○			○		○
		NAPWTH-4 × 30-10-K			○			○			○		○
		NAPWTH-4 × 30-15-K			○			○			○		○
金属配件	横向接口	NAPWYH-4 × 10-3-K	○			○		○					
		NAPWYH-4 × 10-10-K	○			○		○					
		NAPWYH-4 × 10-15-K	○			○		○					
		NAPWYH-4 × 20-3-K		○			○			○		○	
		NAPWYH-4 × 20-10-K		○			○			○		○	
		NAPWYH-4 × 20-15-K		○			○			○		○	
		NAPWYH-4 × 30-3-K			○			○			○	○	
		NAPWYH-4 × 30-10-K			○			○			○	○	
		NAPWYH-4 × 30-15-K			○			○			○	○	